Hess Grade: 1 x 3/4 MN

ADDITIONAL GRADE SHARING THESE SPECS: 1 x 3/4

PARTICLE SIZE SPECIFICATION GRADE 1 x 34MN

SIZE			ALLOWABLE
MICRON	MM	U.S. MESH	PERCENT PASSING
25333	25.333	1	95-100
4750	4.75	4	0-20

TEST METHOD: ASTM C136-06

LOOSE BULK DENSITY GRADE 1x4MN

45 lb/per cubic foot (dry) [1025 kg/per cubic meter] (ASTM C29)



HP Grade one by three-quarters inch stones with some adhered fines.

*MINE GRADES are crushed and screened at the mine and are not dried for packaging in palleted production bags, but rather available in bulk quantities.

GRADE APPLICATIONS

- Air filtration media
- Decorative mulch
- · Lightweight geotechnical fill

PACKAGING OPTIONS

- 2 lb [1 kg] resealable bags
- 20 lb [9 kg] box
- 50 lb [22.6 kg] bags (palleted)
- 1000 lb [454 kg] super sacks (palleted)
- 2200 lb [998 kg] super sacks (palleted)
- Bulk shipped in rail car or tractor trailer

ORDER

- Samples, small quantities, and single production bags (up to 3): order direct from the **PumiceStore.com**
- Partial pallets, full pallets, truckloads: contact us at sales@hesspumice.com or call 208-766-4777

PUMICE TECHNICAL DATA

Chemical analysis, physical properties, and other common data shared by all Hess Pumice grades are detailed on back.



(208) 766-4777 • www.hesspumice.com

Mining and refining the purest commercial deposit of white pumice on the planet.

Hess Pumice Technical Data

CHEMICAL ANALYSIS AND **PHYSICAL PROPERTIES**

Chemical Name: Amorphous Aluminum Silicate

TYPICAL ANALYSIS

- Silicon Dioxide: 76.2%
- Aluminum Oxide: 13.5%
- Ferric Oxide: 1.1%
- Ferrous Oxide: 0.1%
- Sodium Oxide: 1.6%
- Potassium Oxide: 1.8%
- Calcium Oxide: 0.8%
- Titanium Oxide: 0.2%
- Magnesium Oxide: .05%
- Moisture: <1.0%
- Crystalline Si0₂: None Detected

GENERAL PROPERTIES

- Appearance: White powder
- Hardness (MOHS): 6
- pH: 7.2
- · Radioactivity: None
- Softening Point: 900 degrees C
- Water Soluble Substances: 0.15%
- · Loss on Ignition 5%
- GE Brightness: 84
- Specific Gravity: 2.2
- Reactivity: Inert

(except in the presence of calcium hydroxide or hydrofluoric acid)



DESCRIPTION

Amorphous (non-crystalline) in structure and composed primarily of aluminum silicate, pumice is a naturally calcined volcanic glass foam consisting of highly vesicular strands permeated with tiny air bubbles. It is these frothy, friable glass vesicles that, when carefully refined to various grades, give pumice its unique and infinitely useful qualities.

NOTES

- Chemical analysis and physical properties provided are common to all raw Hess pumice grades.
- Grade Variety. The natural, hardyet-friable character of our pumice combined with our crushing and screening expertise allow us to offer pumice grades and grade blends down to 3 microns.
- Safe to Use. No hazardous crystalline structure: testing for crystalline silica (airborne particles of respirable size) finds no measurable Crystalline Silica (SiO₂) present. Free of heavy metals, pesticides, nano-particles, allergens. Certified organic input material.
- **Purity**: As the result of centuries of wave action from a now-extinct inland sea, our pumice is remarkably pure. Our mine grades are typically comprised of 98% pumice and 2% other igneous minerals, which are not removed through our mining processes.
- Storage: Keep dry and protected from the elements until use.



www.hesspumice.com